

AlcoWise AW05

The AW05 is our most cost efficient device in our range of alcohol breathalyzers. The AW05 uses the reliable fuel cell sensor technology to guarantee a reliable alcohol test for a period of 12 months or 500 tests.





The AW05 is extremely compact and fits in any pocket or handbag. The clearly readable LCD screen gives an accurate value in 2 decimal. In addition to a value, the LED also gives a light signal, green when tested below the limit and red when tested above the limit (0.3 g/L BAC).

There is also an LED signal when the batteries are in danger of running out. In short, the AW05 is a versatile device at a low price.

Features:

- Electrochemical fuel cell sensor
- Backlit 3-digit LCD display
- Battery indication
- Result in promille ‰ (g/L BAC)
- Display how many times used
- Switches off automatically

Scope of delivery:

- 1x AW05 alcohol tester
- 2x 1.5V AAA size batteries
- 3x Mouthpieces
- Instructions for use and luxury box packaging

1



Specifications:

Sensor fuel cell Unit of measurement % (g/L BAC) Measuring range in g/L Accuracy ±0,005 % BAC or 0,050 % BAC Dimension (hxwxd in mm) 111x35x24 Weight (g) incl batt. 52 Operating temperature 5~40 °C Storage temperature 0~40 °C Breath sample 5 sec. Warm-up time (1st test) <35 seconds Analysis time 3~22 seconds Display Backlit screen with 3 digit LED Memory slots 0 Display number of tests yes Batteries 2 x 1.5V AAA Number of tests (new batt.) 500 Battery indication yes Automatic power off after 4 seconds Printer connection Nee Mouthpieces 3pcs delivered		
Measuring range in g/L Accuracy ± 0,005 % BAC or 0,050% BAC Dimension (hxwxd in mm) 111x35x24 Weight (g) incl batt. 52 Operating temperature 5°-40°C Storage temperature 0°-40°C Breath sample 5 sec. Warm-up time (1st test) Analysis time 3°-22 seconds Display Backlit screen with 3 digit LED Memory slots 0 Display number of tests yes Batteries 2 x 1.5V AAA Number of tests (new batt.) Soo Battery indication yes Automatic power off after 4 seconds Printer connection Nee	Sensor	fuel cell
Accuracy	Unit of measurement	‰ (g/L BAC)
Dimension (hxwxd in mm) 111x35x24 Weight (g) incl batt. 52 Operating temperature 5~40°C Storage temperature 0~40°C Breath sample 5 sec. Warm-up time (1st test) Analysis time 3~22 seconds Display Backlit screen with 3 digit LED Memory slots 0 Display number of tests yes Batteries 2 x 1.5V AAA Number of tests (new batt.) 500 Battery indication yes Automatic power off after 4 seconds Printer connection Nee	Measuring range in g/L	0.00 - 4.00
Weight (g) incl batt. 52 Operating temperature 5~40°C Storage temperature 0~40°C Breath sample 5 sec. Warm-up time (1st test) < 35 seconds	Accuracy	± 0,005 ‰ BAC or 0,050% BAC
Operating temperature 5~40°C Storage temperature 0~40°C Breath sample 5 sec. Warm-up time (1st test) <35 seconds Analysis time 3~22 seconds Display Backlit screen with 3 digit LED Memory slots 0 Display number of tests yes Batteries 2 x 1.5V AAA Number of tests (new batt.) 500 Battery indication yes Automatic power off after 4 seconds Printer connection no PC connection Nee	Dimension (hxwxd in mm)	111x35x24
Storage temperature 0~40°C Breath sample 5 sec. Warm-up time (1st test) <35 seconds Analysis time 3~22 seconds Display Backlit screen with 3 digit LED Memory slots 0 Display number of tests yes Batteries 2 x 1.5V AAA Number of tests (new batt.) 500 Battery indication yes Automatic power off after 4 seconds Printer connection no PC connection Nee	Weight (g) incl batt.	52
Breath sample 5 sec. Warm-up time (1st test) <35 seconds Analysis time 3~22 seconds Display Backlit screen with 3 digit LED Memory slots 0 Display number of tests yes Batteries 2 x 1.5V AAA Number of tests (new batt.) 500 Battery indication yes Automatic power off after 4 seconds Printer connection no PC connection Nee	Operating temperature	5~40°C
Warm-up time (1st test) < 35 seconds Analysis time 3~22 seconds Display Backlit screen with 3 digit LED Memory slots 0 Display number of tests yes Batteries 2 x 1.5V AAA Number of tests (new batt.) 500 Battery indication yes Automatic power off after 4 seconds Printer connection no PC connection Nee	Storage temperature	0~40°C
Analysis time 3~22 seconds Display Backlit screen with 3 digit LED Memory slots 0 Display number of tests yes Batteries 2 x 1.5V AAA Number of tests (new batt.) 500 Battery indication yes Automatic power off after 4 seconds Printer connection no PC connection Nee	Breath sample	5 sec.
Display Backlit screen with 3 digit LED Memory slots 0 Display number of tests yes Batteries 2 x 1.5V AAA Number of tests (new batt.) 500 Battery indication yes Automatic power off after 4 seconds Printer connection Nee	Warm-up time (1st test)	< 35 seconds
Memory slots 0 Display number of tests yes Batteries 2 x 1.5V AAA Number of tests (new batt.) 500 Battery indication yes Automatic power off after 4 seconds Printer connection no PC connection Nee	Analysis time	3~22 seconds
Display number of tests Batteries 2 x 1.5V AAA Number of tests (new batt.) 500 Battery indication yes Automatic power off after 4 seconds Printer connection no PC connection Nee		
Batteries 2 x 1.5V AAA Number of tests (new batt.) 500 Battery indication yes Automatic power off after 4 seconds Printer connection no PC connection Nee	Display	Backlit screen with 3 digit LED
Number of tests (new batt.) 500 Battery indication yes Automatic power off after 4 seconds Printer connection no PC connection Nee		
Battery indication yes Automatic power off after 4 seconds Printer connection no PC connection Nee	Memory slots	0
Automatic power off after 4 seconds Printer connection no PC connection Nee	Memory slots Display number of tests	o yes
Printer connection no Nee	Memory slots Display number of tests Batteries	0 yes 2 x 1.5V AAA
PC connection Nee	Memory slots Display number of tests Batteries Number of tests (new batt.)	0 yes 2 x 1.5V AAA 500
	Memory slots Display number of tests Batteries Number of tests (new batt.) Battery indication	0 yes 2 x 1.5V AAA 500 yes
Mouthpieces 3pcs delivered	Memory slots Display number of tests Batteries Number of tests (new batt.) Battery indication Automatic power off	yes 2 x 1.5V AAA 500 yes after 4 seconds
	Memory slots Display number of tests Batteries Number of tests (new batt.) Battery indication Automatic power off Printer connection	yes 2 x 1.5V AAA 500 yes after 4 seconds no
Calibration after 12 months or 500 tests	Memory slots Display number of tests Batteries Number of tests (new batt.) Battery indication Automatic power off Printer connection PC connection	yes 2 x 1.5V AAA 500 yes after 4 seconds no Nee